



NING LIGHTING | DIRECTIONAL LIGHTING



CAMERA SYS = **K7000B** 7.0" LCD Colour System

The 7.0" LCD high-resolution colour monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using a CMOS colour infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 2 cameras.

## **Features and Benefits**

- CMOS 18 LED infrared camera •
- Includes monitor shade
- Two camera expandable •
- Two year warranty

## Components

- M7000B
- C2013B 0
- 6 ECTC20-4

## **Expansion Options**

C2013B

ECTC5-4 (5m), ECTC10-4 (10m), ECTC20-4 (20m)

approvals	CE, RoHS
internal controller	Yes
colour	Yes
voltage	12-24
power consumption (W)	5
audio	No
day / night light sensor	Yes
dimensions	174 x 114 x 24mm
weight	0.4kg
temperature	-20 to +70°C
screen size	7.0″
mirror image	Yes
sunshade	Yes
max cameras	2
4 pin camera connection	Yes





Camera Only

FCC CE RoHS (P69K

Camera Only

M7000B

approvals	IP69K, FCC, CE, RoHS
colour	Yes
power consumption (W)	1
microphone	No
day / night light sensor	Yes
dimensions	74 x 76 x 67mm
weight	0.3kg
temperature	-30 to +70°C
lens angle	120°
lens size	1/4″
infrared LEDs	18
mechanical vibration	8G
4 pin camera connection	Yes (threaded connection)

